

# Model 2812 Pump



For situations with more flow Active Water has the solution with the Zoeller model 2812 dual stage macerator pump. Fully certified with RCM and NSF46 certification this pump also comes in a three phase options. The model 2812 comes with a rockwell hardened radial cutter for superior cutting.



- ✓ Higher flows, more design flexibility
- ✓ RCM and NSF certified
- ✓ 2 stage semi open impeller
- ✓ Runs cooler, longer life
- ✓ Rockwell hardened c55 – 60

PUMP		Material
	Pump Housing	Cast iron
	Impeller	Standard Ductile Iron
	Shaft Seal	Silicon Carbide
	Seal	Neoprene
	Bearings	High Carbon chrome steel
	Power Cord	H07RN – F
PUMP		Design Features
	Impeller	Semi Open
	Bearings	Upper and Lower
	Power Cord Length	10m (33') standard
MOTOR		
	Motor Housing	Cast iron
	Type	Permanent split capacitor
	RPM	2850
	Motor Shaft	SS410
	Insulation Class	NEMA B
	Motor Protection	Thermal overload protection
	Protection Class	IP68
	Cooling	Oil filled
	<b>Maximum Fluid Temperature</b>	40°C continuous / 60°C intermittent
	<b>Discharge Size</b>	1-1/4" BSP
	<b>Max. Submersion Depth</b>	6m (20')
	<b>Hardware</b>	Stainless steel
	<b>Cutter/Cutter Plate</b>	440C Stainless steel/RockWell C 55-60

